

Luminaire


Code 0213W10APP
Name CALIPSO S 2700K - APP COMPATIBILE

Measurem.

Code FTS1702505
Name CALIPSO S 2700K - APP COMPATIBILE

Luminaire Flux	2884 lm	Luminaire Power	55.0 W	Efficacy	52.430 lm/W	Efficiency	100.00%
Source Flux	2884 lm	Maximum value	504.37 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	530 mm	Height	50 mm		
Round Luminous Area		Diam.	530 mm	Height	0 mm		
Horizontal Luminous Area		0.220618 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.053372 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		04-12-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2884 lm	
LED Flux=5188,32lm LED Power=50W Eff=56% EfcLed=104lm/W EfcLum=52lm/W CCT=2700K Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	58 86 97 100 100			D DIN 5040	A40		
F UTE	1.00 D			B NBN	BZ 3		

Diam=530mm




Semipiani C

180.0 ——— 0.0

ULOR 0.20 %

DLOR 99.80 %

RN 0.20 %



Luminaire

Code 0213W10APP
Name CALIPSO S 2700K - APP COMPATIBILE

Measurem.


Code FTS1702505
Name CALIPSO S 2700K - APP COMPATIBILE

Luminaire Flux	2884 lm	Luminaire Power	55.0 W	Efficacy	52.430 lm/W	Efficiency	100.00%
Source Flux	2884 lm	Maximum value	504.37 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	530 mm	Height	50 mm		
Round Luminous Area		Diam.	530 mm	Height	0 mm		
Horizontal Luminous Area		0.220618 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.053372 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		04-12-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2884 lm	
LED Flux=5188,32lm LED Power=50W Eff=56% EfcLed=104lm/W EfcLum=52lm/W CCT=2700K Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	58 86 97 100 100			D DIN 5040	A40		
F UTE	1.00 D			B NBN	BZ 3		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.91	1.82	2.73	3.64	4.54	OC	0.91	1.82	2.73	3.64	4.54
OB	0.91	1.82	2.73	3.64	4.54	OD	0.91	1.82	2.73	3.64	4.54

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1454.43	1438.71	1317.69	1119.21	905.21	658.40	424.75	237.73	115.51	36.78
OB	1454.43	1438.71	1317.69	1119.21	905.21	658.40	424.75	237.73	115.51	36.78
OC	1454.43	1438.71	1317.69	1119.21	905.21	658.40	424.75	237.73	115.51	36.78
OD	1454.43	1438.71	1317.69	1119.21	905.21	658.40	424.75	237.73	115.51	36.78



H[m]	D[m]	Max lux	Med lux	Alpha=42.3°+42.3°	G=0.0
1.00	1.82	1454	559		
2.00	3.64	364	140		
3.00	5.45	162	62		
4.00	7.27	91	35		
5.00	9.09	58	22		