



MINI REO II X 93037

19352 9330 B



AVAILABLE IN

BLACK 19352 9330 B

FLEMISH BRONZE OUTDOOR 19352 9330 FBRX

ANTHRACITE 19352 9330 N

WHITE 19352 9330 W



[View on website](#)

General info

LOCATION	indoor-outdoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 56
RECESSED DEPTH (MM)	60
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP65
WEIGHT (KG)	0.3
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WFL-37° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 52) / 3000K / 734-1018lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	Wide (34°-49°)
LED TECHNICS (LIGHT SOURCE)	1018lm // 8,6W // 118lm/W
LED TECHNICS (LUMINAIRE)	709lm // 9,9W // 72lm/W

Requirements



LED POWER SUPPLY 350 / 500mA-DC DIM

For detailed installation instructions, please consult the manual : [19352_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	-
 Concrete + plaster	-
 Lintel + plaster	-
 Hollow-core slab	-
 Hollow-core slab + plaster	-
 Stretched ceiling	-











FINISH YOUR SPECIFICATION

LED power supplies		#
	300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1	2 ☐
	300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	2 ☐

DELTALIGHT

MINI REO II X 93037










19352 9330 B

	300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL	2	☐
	300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL	2	☐
	300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1	2	☐
	300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	2	☐
	300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL	2	☐
	300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL	2	☐
	300 90 61 LED POWER SUPPLY MULTI-POWER DIM6	2 2	☐
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	4(4) 4(4)	☐
	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7	3(2) 2(1)	☐
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9	2 -	☐

DELTALIGHT

MINI REO II X 93037


19352 9330 B

	300 90 68	LED POWER SUPPLY MULTI-POWER DIM5	2(2) 2(1)	☐
	300 90 69	LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6) 6(4)	☐
	300 90 124	LED POWER SUPPLY MULTI-POWER DIM7	2(2) 2(1)	☐
	300 90 125	LED POWER SUPPLY MULTI-POWER MINI DIM5	2(2) 2(1)	☐
	300 90 135	LED POWER SUPPLY MULTI-POWER HV	3->4 2->4	☐
	21012 0010	LED POWER SUPPLY MULTI POWER	2 2	☐
	21012 0021	LED POWER SUPPLY MULTI POWER DIM1	3 3	☐
	21012 0035	LED POWER SUPPLY MULTI POWER DIM5	3 3	☐
	21012 004W	LED POWER SUPPLY MULTI-POWER WDL	4(4) 4(3)	☐
	21012 005W	LED POWER SUPPLY MULTI-POWER COMPACT WDL	3 3	☐

DELTALIGHT


MINI REO II X 93037

19352 9330 B

	21012 0258	LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8	1	☐
	21012 0268	LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8	2->2	☐
	21012 0278	LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	1	☐
	21012 0288	LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	2->3	☐
	21012 0298	LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	2 2	☐
	21012 0308	LED POWER SUPPLY 350mA / 7,35W DIM8	1	☐
	21012 0318	LED POWER SUPPLY 500mA / 10W DIM8	1	☐
	21012 0480	LED POWER SUPPLY 350mA-DC / 17W IP68	2(2)	☐
	21012 0500	LED POWER SUPPLY 500mA-DC / 24W IP68	2(1)	☐
	21032 0295	LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	2	☐

MINI REO II X 93037

19352 9330 B



21032 0305

LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

2



Notes: