




201083.30.10.GL.0

Hydrofloor Nano All Glass

Round ground-recessed luminaire for outdoor installation flush with the ground, hard anodized black aluminium body and cover/diffuser made entirely in tempered safety glass, moulded silicone gasket. Remote constant current max 700 mA driver needed, with 1 CREE XHP35 HD LED. IP68 rating.



Light Source Technical Data

Wattage	5W (@350mA) / 7W (@500mA) / 10W (@700mA)
CCT	3000K
Beam Angle	10°
Lumens	489 lm (@350mA) / 662 lm (@500mA) / 872 lm (@700mA)
Finish	CLEAR GLASS
Dimming	ON/OFF
IP Rating	IP68
IK Rating	IK09
Coating	Anodized black aluminium
Light Source	1 CREE XHP35 HD LED
Transformer	Constant current max 700 mA
Gasket	Moulded silicone
Glass	CLEAR
Gross Weight	1,10 Kg

Technical Feature



Integrated Accessories

Built-in accessories to be requested when ordering

example 201083.30.10.GL.0.HC


201083.30.10.GL.0. _ _



.00

NO ACCESSORY

No accessory



.HC

honeycomb LOUVER



.GS

STANDARD GLARE SHIELD (AC114)

Glare shield accessory made in hard anodized black aluminum, providing good balance in between glare control and light output.



.SC

SUPER COMFORT GLARE SHIELD (AC115)

Glare shield accessory made in hard anodized black aluminum, for applications requiring very reduced glaring; minimal light loss on the light surface but overall lumen output typically reduced by 50%.

Remote Driver Selection

ALVIT Italy	AL1435S-IP	constant current 350mA	14W	IP67	min 1 max 1
ALVIT Italy	AL1450S-IP	constant current 500mA	14W	IP67	1
ALVIT Italy	AL1470S-IP	constant current 700mA	14W	IP67	1
TCI Italy	152014/350	constant current 350mA	17W	IP68	min 1 max 3
TCI Italy	152014/500	constant current 500mA	24W	IP68	min 1 max 3
TCI Italy	152014/700	constant current 700mA	30W	IP68	min 1 max 3

Gallery

