DELTALIGHT®

ENTERO SQ-S X 92730 B

28539 9240 B

AVAILABLE IN
BLACK 28539 9240 B
FLEMISH BRONZE OUTDOOR 28539 9240 FBRX
FULL WHITE 28539 9240 FW
ANTHRACITE 28539 9240 N





View on website

General info	
LOCATION	outdoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	square - 76 x 76
RECESSED DEPTH (MM)	110
THICKNESS OF MOUNTING SURFACE (MM)	12,5 or 25
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	0.285
ADJUSTABILITY	0° to 20° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 60) / 2700K / 753-1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	649lm // 9,9W // 66lm/W

Requirements

LED POWER SUPPLY 350 / 500mA-DC DIM

Accessories

ENTERO S HONEYCOMB
ENTERO S LINEAR SPREAD LENS
ENTERO S SPREAD LENS
ENTERO S SOFTENING LENS
ENTERO S GLASS SBL

DELTALIGHT®

ENTERO SQ-S X 92730 B

28539 9240 B

For detailed installation instructions, please consult the manual: **28539_XXX0_HAND.pdf**

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
System ceiling	-
Plasterboard	-
Stucanet	-
Wood	-
Stretched ceiling	-

DELTALIGHT®

ENTERO SQ-S X 92730 B

28539 9240 B

FINISH YOUR SPECIFICATION

Emergency units



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

DELTALIGHT®

ENTERO SQ-S X 92730 B

28539 9240 B

LED power supplies

				#
	**300 90 63**	LED POWER SUPPLY MULTI-POWER DIM9	4(4) | 4(4)	
	**300 90 68**	LED POWER SUPPLY MULTI-POWER DIM5	2(2) | 2(1)	
	**300 90 69**	LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6) | 6(4)	
	**300 90 124**	LED POWER SUPPLY MULTI-POWER DIM7	3(2) | 2(1)	
	**300 90 125**	LED POWER SUPPLY MULTI-POWER MINI DIM5	2(2) | 2(1)	
	**21012 0010**	LED POWER SUPPLY MULTI POWER	2 | 2	
	**21012 0021**	LED POWER SUPPLY MULTI POWER DIM1	3 | 3	
	**21012 0035**	LED POWER SUPPLY MULTI POWER DIM5	3 | 3	
	**21012 005W**	LED POWER SUPPLY MULTI-POWER COMPACT WDL	3 | 3	

DELTALIGHT®

ENTERO SQ-S X 92730 B

28539 9240 B

	**21012 0268**	LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8	2->2 | 0
	**21012 0278**	LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	1
	**21012 0288**	LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	2->3
	**21012 0298**	LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	2 | 2
	**21012 0308**	LED POWER SUPPLY 350mA / 7,35W DIM8	1
	**21012 0318**	LED POWER SUPPLY 500mA / 10W DIM8	1
	**21012 0480**	LED POWER SUPPLY 350mA-DC / 17W IP68	2(2)
	**21012 0500**	LED POWER SUPPLY 500mA-DC / 24W IP68	2(1)
	**21032 0295**	LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	2
	**21032 0305**	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	2

ENTERO SQ-S X 92730 B

28539 9240 B

Light altering devices



28500 0010 ENTERO S LINEAR SPREAD LENS

28500 0020 ENTERO S SPREAD LENS



28500 0030 ENTERO S SOFTENING LENS



28500 0040 ENTERO S GLASS SBL



28500 0050 B ENTERO S HONEYCOMB SINGLE USE B

Replaceable reflector / lens



19810 0180 SPY 52 REFLECTOR 20°



19810 0190 SPY 52 REFLECTOR 45°



19810 0240 SPY 52 REFLECTOR 30°

ENTERO SQ-S X 92730 B

28539 9240 B

Notes: