puk

506001.27.FW.03.0

# Passoluce Mini Round

Round shape wall-recessed luminaire with floor-wahser light distribution for outdoor installation, phospho-chromatised and polyester powder coated diecast copper-free aluminium body, tempered sand-blasted glass diffuser, moulded silicone gaskets, polypropylene housing for recess. Remote constant voltage 24V DC power supply needed. IP66 rating.




PUK ITALIA GROUP srl
Via San Giorgio 16
20851 Lissone (MB) – ITALY

T. +39 039 24.57.920
F. +39 039 24.57.924
puk@puk.it – puk.it

# Light Source
# Technical Data

| | |
|---|---|
| **Wattage** | 3W |
| **CCT** | 2700K |
| **Beam Angle** | floor washer |
| **Lumens** | 110 |
| **Finish** | RAL9005 |
| **Dimming** | ON/OFF |
| **IP Rating** | IP66 |
| **IK Rating** | IK08 |
| **Coating** | Polyester powder coating with phosphocromating pre-finish |
| **Screws** | Copper-free aluminium |
| **Transformer** | Constant voltage 24V DC |
| **Gasket** | Moulded silicone |
| **Glass** | Tempered sand-blasted |
| **Gross Weight** | 0,50 Kg |

# Technical Feature

ON OFF | IP 66 | IK 08 | NEW | CE | 5 YEARS

PUK ITALIA GROUP srl
Via San Giorgio 16
20851 Lissone (MB) – ITALY

T. +39 039 24.57.920
F. +39 039 24.57.924
puk@puk.it – puk.it

# Integrated Accessories

Built-in accessories to be requested when ordering

example 506001.27.FW.03.0**.HC**

506001.27.FW.03.0. _ _

.00

NO ACCESSORY

No accessory

PUK ITALIA GROUP srl
Via San Giorgio 16
20851 Lissone (MB) – ITALY

T. +39 039 24.57.920
F. +39 039 24.57.924
puk@puk.it – puk.it

puk

# Remote Driver Selection

| | | | | | |
|---|---|---|---|---|---|
| Meanwell | LPV-20-24 | constant voltage 24V DC | 20W | IP67 | min 1 max 4 |
| Meanwell | LPV-35-24 | constant voltage 24V DC | 35W | IP67 | min 1 max 8 |

# Gallery

PUK ITALIA GROUP srl
Via San Giorgio 16
20851 Lissone (MB) – ITALY

T. +39 039 24.57.920
F. +39 039 24.57.924
puk@puk.it – puk.it