



modello:
model:

ZEPPELIN MINI PLUS QUADRO

codice:
code:

6733

design:

UT Egoluce

anno - year:

2022

tipologia:
typology:

faretto da incasso calpestabile
trampleable recessed spotlight

materiali:
materials:

acciaio INOX AISI 316L
stainless steel AISI 316L

luce:

diretta

light:

direct

sorgente luminosa:
light source:

LED code beams optic

/XW	/11	/25	/45	LED	1W	350mA	138lm	2700K
/WW	/11	/25	/45	LED	1W	350mA	143lm	3000K
/W	/11	/25	/45	LED	1W	350mA	151lm	4000K

grado IP - IP grade:

67

peso netto - net weight:

0,06 Kg

finiture:

.33 acciaio satinato

finishes:

.33 matt steel

marcatura:



marking:

simboli costruttivi:



symbols:



IP67



Dimensioni - Dimensions




SOLO COLLEGAMENTO IN SERIE - ONLY SERIAL CONNECTION

Accessorio - Accessory



0215

Controcassa in materiale plastico
Plastic Box



EGOLUCE s.r.l. via I. Newton 12 - 20016 Pero - Milano
telefono +39 02 339586.1 - fax. +39 02 3535112
e-mail: info@egoluce.com - http://www.egoluce.com

La presente scheda tecnica è di proprietà di EGOLUCE srl. Tutti i diritti sono riservati. Le fotografie, le descrizioni degli apparecchi, i disegni quotati ed i valori fotometrici menzionati sono a titolo indicativo e non costituiscono alcun impegno per la nostra società che si riserva di apportare, in qualsiasi momento e senza preavviso, tutte le modifiche che riterrà opportune.

LED DRIVERS in corrente continua LED DRIVERS constant current

0125

LED driver

IN: 100 - 240V
OUT: 350 mA
1-6 Power LED




SELV

6 x 3,5 x 2 cm 4 cm

0128

LED driver

IN: 100 - 240V
OUT: 350 mA
1-10 Power LED




11,6 x 3,4 x 2 cm 4 cm SELV CLASS 2

0136/15

LED driver

IN: 100 - 240V
OUT: 350 mA
1-10 Power LED 1W




15,8 x 2,2 x 2 cm 3,2 cm SELV

0169/50

Multipower LED driver

IN: 220 - 240V
OUT: 350mA
min. 4 - max 22 Power LED




13 x 7,5 x 3 cm 8,5 cm SELV

DRIVERS DIMMERABILI in corrente continua DIMMABLE LED DRIVERS constant current

0129 Dimmer LED

Multipower dimmable driver

IN: 110 - 240V
OUT: 350 mA
4-15 Power LED




10,5 x 7 x 2,2 cm 7,2 cm SELV

0129/DALI Dimmer LED

Multipower dimmable driver

IN: 110 - 240V
OUT: 350 mA
2-12 Power LED




10,5 x 7 x 2,2 cm 7,2 cm SELV

0141/DALI

LED driver

IN: 110 - 240V
OUT: 350 mA
1-12 Power LED




11,1 x 5,2 x 2,5 cm 5,5 cm

0141/DIM

LED driver

IN: 110 - 240V
OUT: 350 mA
1-12 Power LED




Versione PUSH non sincronizzabile - PUSH version not synchronizable

11,1 x 5,2 x 2,5 cm 5,5 cm

0145 Dimmer LED Maxi

Multipower dimmable driver

IN: 110 - 240V
OUT: 350 mA
1- 21 Power LED




12,3 x 8 x 2,2 cm 8,4 cm SELV

0145/DALI Dimmer LED Maxi

Multipower dimmable driver

IN: 110 - 240V
OUT: 350 mA
1- 21 Power LED



12,3 x 8 x 2,2 cm 8,4 cm SELV

0133

Cavo di sincronizzazione per dimmer LED

Synchronization cable for dimmer LED

(art. 0129 - art. 0129/DALI - art. 0145 - art. 0145/DALI)




L 150 cm

0726/DIM

LED dimmer

TAGLIO DI FASE (IGBT-TRIAC, TRAILING EDGE-LEADING EDGE)
PHASE CUT-OFF (IGBT-TRIAC, TRAILING EDGE-LEADING EDGE)
IN: 220 - 240V
OUT: 24V - 20W
350 mA
1-12 Power LED




16,5 x 4,5 x 3,5 cm 5,6 cm IGBT-TRIAC SELV

IP LED DRIVERS in corrente continua IP LED DRIVERS constant current

0031/IP

LED driver

IN: 220 - 240V
OUT: 350 mA
1-12 Power LED 1W



3,9 x 8 x 2 cm 4,2 cm IP67 SELV

