puk

904001.27.DF.07.0

Vetra Dot 600

Designed by

NAVA + AROSIO

Featuring a minimalist stainless-steel bollard structure and a distinctive glass element that softens and diffuses the emitted light. All structural parts are phospho-chromatised and polyester powder coated. Total height 620 mm. Remote constant voltage 24V DC power supply needed. IP66 rating.

PUK ITALIA GROUP srl
Via San Giorgio 16
20851 Lissone (MB) – ITALY

T. +39 039 24.57.920
F. +39 039 24.57.924
puk@puk.it – puk.it

puk

Light Source
Technical Data

Wattage	3W
CCT	2700K
Beam Angle	diffused
Lumens	110
Finish	Obsidian Black
Dimming	ON/OFF
IP Rating	IP66
Coating	Polyester powder coating with phosphocromating pre-finish
Screws	Stainless steel
Transformer	Constant voltage 24V DC
Glass	CLEAR
Gross Weight	0,70 Kg

Technical Feature

ON OFF | IP66 | NEW | CE | 5 YEARS | DALI

PUK ITALIA GROUP srl
Via San Giorgio 16
20851 Lissone (MB) – ITALY

T. +39 039 24.57.920
F. +39 039 24.57.924
puk@puk.it – puk.it

Integrated Accessories

Built-in accessories to be requested when ordering

example 904001.27.DF.07.0**.HC**

904001.27.DF.07.0. _ _

.00

NO ACCESSORY

No accessory

PUK ITALIA GROUP srl
Via San Giorgio 16
20851 Lissone (MB) – ITALY

T. +39 039 24.57.920
F. +39 039 24.57.924
puk@puk.it – puk.it

Remote Driver Selection

Meanwell	LPV-20-24	constant voltage 24V DC	20W	IP67	min 1 max 4
Meanwell	LPV-35-24	constant voltage 24V DC	35W	IP67	min 1 max 8

Gallery

PUK ITALIA GROUP srl
Via San Giorgio 16
20851 Lissone (MB) – ITALY

T. +39 039 24.57.920
F. +39 039 24.57.924
puk@puk.it – puk.it