

FLOS

09.3201.BZA Bronze

G-O Amber Light

Designed by Jorge Herrera, 2017



Semi recessed signalling lamp for indoor use on ceiling/wall. Power supply not included. 1000 mm power cable included.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Wall recessed
Environment	Indoor dry location
LED type	Top LED
Lamp category	LED
Ilcos	No
Power (W)	1.2
Source flux (lm)	96
System flux (lm)	2

Physical

Colour	Bronze
Trim	No
Orientation	Fixed
Recessed depth (mm)	56
Net weight (kg)	0.2
IP	20
IP external	65



Download

Mounting instructions [Download PDF](#)

Photometric Files

LDT / IES [Download ZIP](#)


Technical Drawings

2D [Download ZIP](#)

3D [Download ZIP](#)



Schematic light drawing



Photometric

Lighting type	Indirect, Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	72
Beam angle C90-270 (°)	72

Electrical

Insulation class	III
Frequency (Hz)	50/60
Driver	Remote excluded
Dimmable	Yes
Dimming type	Non Dimmable, Dimmable DALI 1
Emergency type	No

Notes

Equipment for remote installation in an accesible place: it does not fit through the luminarie installation hole. For Dali installation, the non-dimmable kit and the Dali controller are needed.

Accessories & Power Supply



REQUIRED
Power supply

60.9157

Electronic transformer with constant voltage (24V) for LED. 8W, 110/240V, 50/60H



REQUIRED
Power supply

60.8703

Electronic transformer with constant voltage (24V) for LED. 100/240V, 25W



OPTIONAL
Accessory

08.8422.00

Prepared for recessing



OPTIONAL
Accessory

60.8640

Dimmable 1-10V control unit with 1 channel for 24V LED modules. Max. 120W - 5A



OPTIONAL
Accessory

Electrical

60.9766

Dimmable Dali 2 control unit for 12-48Vdc LED modules