

Light Bell No Dimmable

Designed by Piero Lissoni, 2017



Suspended luminaire for mounting on the ceiling with LED light source. (4 metres maximum distance to ceiling). Power supply source integrated into luminaire housing. Reflector not included; supplied separately.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Suspension
Environment	Indoor dry location
LED type	LED array
Lamp category	LED
Ilcos	No
Number of heads	1
Power (W)	55
Source flux (lm)	6388

Physical

Colour	Black
Trim	No
Orientation	Fixed
Net weight (kg)	3.81
IP	20



Download

Mounting instructions [ZIP](#)

Photometric Files

LDT / IES [ZIP](#)


Technical Drawings

2D [ZIP](#)

3D [ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
Beam angle C0-180 (°)	78
Beam angle C90-270 (°)	78

Electrical

Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	35.20
Driver	Integrated
Dimmable	No
Dimming type	Non Dimmable
Emergency type	No

Notes

Pin-block type dissipater. Please ask us for a higher IP. Includes a 4-meter suspension cable.

Accessories & Power Supply



OPTIONAL
Accessory
07.9630.AN
Light Bell



OPTIONAL
Accessory
07.9630.18
Light Bell



OPTIONAL
Accessory
07.9630.70
Light Bell



OPTIONAL
Accessory
07.9630.76
Light Bell



OPTIONAL
Accessory
07.9630.7C
Light Bell



OPTIONAL
Accessory
07.9630.AP
Light Bell



OPTIONAL
Accessory
07.9630.CE
Light Bell



OPTIONAL
Accessory
08.8775.40
Rosette



OPTIONAL
Accessory

F0556020

Rosette for indoors. IP20. Non
Dimmable



OPTIONAL
Accessory

F0557020

Rosette for indoors. IP20.
Dimmable Push/Dali



OPTIONAL
Accessory

08.8775.14

Rosette