

Bon Jour Ø 145 Dali


Designed by Philippe Starck, 2016



Recessed luminaire with LED light source. Remote 110/240V power supply included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Recessed
Enviroment	Indoor dry location
LED type	LED array
Lamp category	LED
Lamp holder	LED Module
Number of heads	1
System power (W)	36
Source flux (lm)	3845
System flux (lm)	891

Physical

Colour	Copper
Trim	Yes
Recessed depth (mm)	205
Bezel diameter (mm)	145
Net weight (kg)	1.11
Package volume (m3)	0.01
IP internal	20
IP external	44

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[Bim](#) [↓ ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
Beam angle C0-180 (°)	49
Beam angle C90-270 (°)	49
UGR _L	11

Electrical


Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	110/240
LED current (mA)	900
Driver	Remote included
Dimmable	Yes
Dimming type	Dimmable DALI 2
Dimming interface	Remote Dimmable (Dimmer Not Included)

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **G**



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

Pre-installation frame must be ordered separately

Accessories & Power Supply



REQUIRED
Frame

08.8975.00

Pre-installation frame