

Light Supply Fixed Trim

Designed by FLOS Architectural, 2014


LED - Phosphor LED - 26W - 1158lm - 3000K - CRI> 98 - Beam° 49

Recessed luminaire with LED light source. Remote 220/240V power supply included.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Ceiling recessed
Enviroment	Indoor dry location
LED type	Phosphor LED
Lamp category	LED
Ilcos	No
Number of heads	1
Power (W)	26
Source flux (lm)	2371
System flux (lm)	1158

Physical

Colour	White/Aluminium
Trim	No
Orientation	Fixed
Recessed depth (mm)	277
Net weight (kg)	0.98
IP internal	20
IP external	44

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[Bim](#) [↓ ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	98
Beam angle C0-180 (°)	49
Beam angle C90-270 (°)	49

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220.00
Driver	Remote included
Dimmable	No
Dimming type	Non Dimmable
Emergency type	No