

FLOS

FA53122433 Anthracite

Emma Ceiling 4 NEW


Designed by FLOS Outdoor



LED source included. Integrated power supply 220-230V ON/OFF and dimmable 1-10V or DALI. With IP65 cable guide for rubber cables 5mm<ø<9mm and a connection box for fast connections. To ensure the tightness of the cable guide it's recommended to use flexible electric cables suitable for exterior use.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling
Enviroment	Outdoor wet location
LED type	LED array
Lamp category	LED
Number of heads	1
Power (W)	17
System power (W)	20
Source flux (lm)	2387
System flux (lm)	1907

Physical

Colour	Anthracite
Orientation	Fixed
IP internal	65

Download

Mounting instructions [ZIP](#)


Photometric Files

LDT / IES [ZIP](#)


Technical Drawings

2D [ZIP](#)

3D [ZIP](#)



Schematic light drawing



Photometric


Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	80
Beam angle C0-180 (°)	20
Beam angle C90-270 (°)	20

Electrical


Insulation class	I
Frequency (Hz)	50-60
Main voltage (Vac)	220-240
Dimmable	No
Dimming type	Non Dimmable
Emergency type	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

Accessories & Power Supply



OPTIONAL Accessory

F990C040000

2 way terminal block 4 poles

IP68. (ø7÷12mm cable).