

FLOS



F9514044 Pink Cable/Gold Ring

Wirering Pink

Designed by Formafantasma, 2018

16W - 712lm - 2700K - CRI> 90

Indirect light wall lighting device with body in calendered, extruded aluminium with galvanised or varnished finish. The special tangent cable, in coloured rubber, provides the power. The cable is fixed to the wall with ABS joints in the same finish as the ring. Dimming via switch pedal on the cable. Power supply on adapter with interchangeable plugs. Useful cable length is 2.5 metres.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

EAN	8059607007815
Mounting	Wall
Enviroment	Indoor dry location
Light source type	LED
LED type	LED Module
Power (W)	16
System flux (lm)	712

Physical

Colour	Pink Cable/Gold Ring
Length (mm)	317
Cord length (mm)	2500
Net weight (kg)	0.95
Package volume (m3)	0.02
IP internal	20



Download

Mounting instructions  PDF

Spare Parts  PDF

Photometric Files

LDT / IES  LDT


Technical Drawings

2D  ZIP

3D  ZIP



Schematic light drawing



Photometric


Lighting type	Indirect
Light distribution	Asymmetric
CCT (K)	2700
CRI>	90

Electrical


Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	100-240/24
Driver	Remote included
Dimmable	Yes
Dimming type	Electronic 24V
Dimming interface	Dimmer Integrated
Plug type	Type G, Type A, Type C
Batteries inside	No
Charging min time	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user

Spare Parts



RF26677
Ring assembly



RF3320100
Black plug assembly kit & 24V driver



RF9510400
Kit with screws, nuts and components



RF26646
Electrical mounting assembly with dimmer



RF26651
Electrical mounting body assembly