

FLOS


 F0414030 Black

Arrangements Drop Up

Designed by Michael Anastassiades, 2018

32W - 1530lm - 2700K

Diffuse light suspended lighting device. Body in extruded, curved NC-machined and black powder-coated aluminium, diffuser in platinum optical silicone. Each component can be connected to the power pack by means of an electrical and mechanical connection system designed for customisable product set-up. Roses available with two powers: lamp with power under 70W and lamp with power under 190W. Class III roses also available for installations with remote power supply: "surface" version for installations on cement, "recessed" version for plasterboard ceilings. The electronics integrated in the rose enables use of dimming systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the light flow can be set with the push system included in the rose. Cable length 2.4m



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

EAN	8059607014165
Mounting	Suspension
Enviroment	Indoor dry location
Light source type	LED
LED type	LED Module
Power (W)	32
System flux (lm)	1530

Physical

Colour	Black
Cord length (mm)	2500
Net weight (kg)	0.65
Package height (cm)	45
Package width (cm)	545
Package length (cm)	755
Package volume (m3)	0.02
IP internal	20

Download

Mounting instructions	↓ PDF
Spare Parts	↓ PDF

Photometric Files

LDT / IES	↓ LDT
---------------------------	-----------------------

Technical Drawings

2D	↓ ZIP
3D	↓ ZIP
Bim	↓ ZIP



<https://professional.flos.com/en/global/product/arrangements-drop-up-f0414030/>


F0414030

©2022 Flos - P.IVA 00290820174 - 3/18/2023

professional.flos.com | info@flos.com 1/3


In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order to improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

Schematic light drawing



Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only)
light source by a
professional


Photometric

Lighting type	Indirect, Direct
Light distribution	Symmetric
CCT (K)	2700

Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	48
LED voltage Vf (Vdc)	null
Driver	Remote
Dimmable	Yes
Dimming type	Electronic 48V
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No
Charging min time	No

Accessories & Power Supply



REQUIRED

F0415030

Arrangements Big Rose



REQUIRED

F0416030

Arrangements Small Rose



REQUIRED

F0418030

Arrangements Recessed Rose