



Three Phase Track Surface/Pendant Dali 1000 mm

Length: 1000 - Surface and suspension



GLOBAL PRO offers benefits for advanced installations: the main connectors are feedable and the feeding cable can be hidden under the elegant suspension accessories. GLOBAL PRO lighting tracks are designed for easy surface mounting on ceilings and walls, or recessed mounting in suspended ceilings. Lighting tracks can be suspended at any desired height. Other advantages of the three-circuit system are its high loading capacity and the possibility of forming independent fixture groups in all three circuits. This permits illumination of the most demanding environments.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Surface and suspension
Environment	Indoor dry location
Icos	No

Physical

Colour	Aluminum
Trim	No
Length (mm)	1000
Net weight (kg)	0.80
IP internal	20
IP external	20

Download

[Mounting instructions](#)

[PDF](#)



Electrical

Insulation class	I
Emergency type	No

Accessories & Power Supply



OPTIONAL
Accessory

60.3016.11

Blind end



OPTIONAL
Accessory

60.3008.11

Attachment on track for steel
cable suspension with M6 thread
end



OPTIONAL
Accessory

60.3008.14

Attachment on track for steel
cable suspension with M6 thread
end



OPTIONAL
Accessory

60.3043.29ADA

Mean connector Dali



OPTIONAL
Accessory

60.3057.29

Attachment on track for wire
suspension



OPTIONAL
Accessory

60.3093.29

Bracket for fixing track to wall or
ceiling



OPTIONAL
Accessory

60.3028.29ADA

Connector 90° Outside Dali



OPTIONAL
Accessory

60.3043.14ADA

Mean connector Dali



OPTIONAL
Accessory

60.3094.11

Ceiling fitting with rose



OPTIONAL
Accessory

60.3057.11

Attachment on track for wire
suspension



OPTIONAL
Accessory

60.3029.29ADA

Connector 90° Inside Dali



OPTIONAL
Accessory

60.3036.11ADA

Cross Coupling Dali



OPTIONAL
Accessory

60.3048.14ADA

Connector T - Inside Left Dali



OPTIONAL
Accessory

60.3029.14ADA

Connector 90° Inside Dali



OPTIONAL
Accessory

Mounting

60.3014.11

Suspension rod with 1 m rose.
M6 thread



OPTIONAL
Accessory

Mounting

60.3014.14

Suspension rod with 1 m rose.
M6 thread



OPTIONAL
Accessory

60.3029.11ADA

Connector 90° Inside Dali



OPTIONAL
Accessory

60.3036.14ADA

Cross Coupling Dali



OPTIONAL
Accessory

60.3048.29ADA

Connector T - Inside Left Dali



OPTIONAL
Accessory

60.3047.11ADA

Connector T - Inside Right Dali



OPTIONAL
Accessory

60.3044.11ADA

Straight Connector Dali



OPTIONAL
Accessory

60.3028.11ADA

Connector 90° Outside Dali



OPTIONAL
Accessory

60.3044.12ADA

Straight Connector Dali



OPTIONAL
Accessory

60.3048.11ADA

Connector T - Inside Left Dali



OPTIONAL
Accessory

60.3016.12

Blind end



OPTIONAL
Accessory

60.3016.14

Blind end



OPTIONAL
Accessory

60.3028.14ADA

Connector 90° Outside Dali



OPTIONAL
Accessory

60.3018.11

Attachment on track for rod
suspension M6 thread



OPTIONAL
Accessory

60.3092.11

Power supply rose cover



OPTIONAL
Mounting

60.3097.14

1 m suspension rod with ceiling
rose with m6 thread



OPTIONAL
Accessory

60.3044.14ADA

Straight Connector Dali



OPTIONAL
Mounting

60.3097.11

1 m suspension rod with ceiling
rose with m6 thread



OPTIONAL
Accessory

60.3096.29

Lead-weighted wire 3000 mm



OPTIONAL
Accessory

60.3054

Lead bending key



OPTIONAL
Accessory

60.3018.14

Attachment on track for rod
suspension M6 thread



OPTIONAL
Accessory

60.3025.29

Bracket



OPTIONAL
Accessory

60.3090.11

Track cover strip L 3000 mm



OPTIONAL
Accessory

60.3094.14

Ceiling fitting with rose



OPTIONAL
Accessory

60.3047.14ADA

Connector T - Inside Right Dali



OPTIONAL
Accessory

60.3047.29ADA

Connector T - Inside Right Dali



OPTIONAL
Accessory

60.3095.29

Lead-weighted wire 1500 mm



OPTIONAL
Accessory

60.3025.11

Bracket



OPTIONAL
Accessory

60.3043.11ADA

Mean connector Dali



OPTIONAL
Accessory

60.3036.29ADA

Cross Coupling Dali



OPTIONAL
Accessory

60.3025.14

Bracket



OPTIONAL
Accessory

60.3083.29

Complete wall support 70 mm