

Fort Knox Ceiling

Designed by Philippe Starck, 2016




LED - LED array - 9.2WW - 860lm - 3000K - CRI> 80 - Beam° 27

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling surface
Enviroment	Indoor dry location
LED type	LED array
Lamp category	LED
Ilcos	No
Number of heads	1
Power (W)	9.2W
Source flux (lm)	1178
System flux (lm)	860

Physical

Colour	White
Trim	No
Orientation	Adjustable
Rotation (°)	355
Longitudinal tilting (°)	95
Net weight (kg)	0.70
IP	20
IP external	20

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)


Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	80
Beam angle C0-180 (°)	27
Beam angle C90-270 (°)	27

Electrical

Insulation class	I
Frequency (Hz)	50/60
Driver	Integrated
Dimmable	No
Dimming type	Non Dimmable
Emergency type	No