

Zero Track Surface Profile

Designed by Flos Architectural, 2018



Electro-mechanical indoor profile for surface installation (ceiling or wall). To be fixed with specific screw plugs that come with the profile.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Surface
Enviroment	Indoor dry location
Ilcos	No

Physical

Colour	Bronze
Trim	No
Length (mm)	1000
Net weight (kg)	0.21
IP	20



Download

Mounting instructions

 PDF



Electrical

Insulation class	III
Main voltage (Vac)	24
LED voltage Vf (Vdc)	24
Driver	Remote excluded
Dimmable	Yes
Dimming type	Non Dimmable, Dimmable Casambi, Dimmable 1-10V, Dimmable DALI 1

Notes

It is necessary to order the power connector, intermediate connectors and covers separately. Feed unit connectors available as 90° flat corner and curve (symmetric element for left/right corner), ceiling/wall - wall/wall inner corner, as well as "T" and "X" shape. For vertical installations, installing the stopper is mandatory. It must be ordered separately.

PWM voltage output dimmable drivers shall be used at frequencies between 250 and 500Hz.

Accessories & Power Supply



REQUIRED

06.2510.CZ

Power supply surface end. 57W - 220/240V



REQUIRED

06.2511.CZ

Power supply surface middle. 57W - 220/240V



REQUIRED

Power supply

Electrical

60.9359

24V Remote power supply. 25W 110/240V



REQUIRED

Power supply

Electrical

60.9360

24V Remote power supply. 36W-110V / 45W-240V



REQUIRED

Power supply

Electrical

60.9443

Power supply LED. 100W - 24V. 100-240V, 50-60Hz.



REQUIRED

Power supply

Electrical

60.9361

24V Remote power supply. 57W 220/240V



REQUIRED

Power supply

Electrical

60.9777

Remote Power Supply Non Dimmable 24V. 120W. 220/240V



REQUIRED

Power supply

Electrical

60.9374

Remote Power Supply Non Dimmable 24V. 60W. 220/240V



REQUIRED
Power supply

Electrical

60.9515

Remote Power Supply Non
Dimmable 24V. 60W. 220/240V



REQUIRED

06.2540.CZ

Zero Track Surface Profile. Feed
Unit for Remote Power Supply
Unit



REQUIRED

Power supply

60.9516

Remote Power Supply Non
Dimmable 24V. 120W. 220/240V



REQUIRED
Profile

06.2509.CZ

Zero Track Surface Profile. End
Cap



OPTIONAL
Corner

06.2543.CZ


Zero Track Surface Profile.
Ceiling/wall - wall/wall inner corner



OPTIONAL
Corner

06.2544.CZ

Zero Track Surface Profile.
Interior ceiling/ceiling-wall/wall
curve



OPTIONAL
Corner

06.2546.CZ

Zero Track Surface Profile. Cross-
shaped connector



OPTIONAL
Accessory

08.0630.14

Stopper



OPTIONAL
Accessory

Electrical

60.9677

Controller DALI or Push Dim



OPTIONAL
Accessory

08.0630.40

Stopper



OPTIONAL
Accessory

Electrical

60.9630

Controller CASAMBI



OPTIONAL
Accessory

Electrical

60.9394

Controller 0/1-10V or Push Dim



OPTIONAL
Corner

06.2545.CZ


Zero Track Surface Profile, T-
shaped connector



OPTIONAL

06.2541.CZ

Zero Track Surface Profile, Feed
intermediate connector



OPTIONAL
Corner

06.2542.CZ

Zero Track Surface Profile, 90°
Flat Corner



OPTIONAL

06.2506.14

Zero Track Surface Profile,
Intermediate Connector



OPTIONAL

06.2506.40

Zero Track Surface Profile.

Intermediate Connector