

FLOS

09.0367.30 White

Spot Module Pro LED Array


Designed by FLOS Architectural



Spotlight to be installed on Light Cut Mini system. Remote continuous current supply source not included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Track
Environment	Indoor dry location
LED type	LED array
Lamp category	LED
Ilcos	No
Power (W)	18
Source flux (lm)	0
System flux (lm)	1699

Physical

Colour	White
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	180
Spot diameter (mm)	60.00
Net weight (kg)	1.2
IP internal	20
IP external	20

Download

[Mounting instructions](#) PDF

[Mounting instructions](#) PDF

Photometric Files


[LDT / IES](#) ZIP

Technical Drawings


[2D](#) ZIP

[3D](#) ZIP

[Bim](#) ZIP



Schematic light drawing



Beam Angle: 37°

h(m)	E(lx)	D(m)
1	4687	0.67
2	1172	1.34
3	521	2.00
4	293	2.67
5	187	3.34

Luminous flux Luminaire
1699 lm

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	37
Beam angle C90-270 (°)	37

Electrical

Insulation class	III
Main voltage (Vac)	34.50
Driver	Remote excluded
Dimmable	Yes
Dimming type	Non Dimmable, Dimmable, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Emergency type	No

Notes

High performance part numbers include high performance reflector.

Accessories & Power Supply



REQUIRED Power supply

60.9188

Continuous current power supply of 13-20W, 110*/240V - 50/60Hz with power current selected through adjustable 300 mA - 15W / 350 mA - 18W / 400/ 450/ 500/ 550/ 600/ 650/ 700/ 750/ 800/ 850/ 900 mA - 20W. switch. 0/1-10V or push dimming. 110V Max 15W



REQUIRED Power supply

60.9160

Non dimmable continuous current power supply of 220/240V - 50/60Hz with power current selected through adjustable with switch 200 mA - 8,5W / 300 mA - 13W / 350 mA - 15W / 400 mA - 17,5W / 450 mA - 19,5W / 500 mA - 22W



REQUIRED Power supply

60.9207

Continuous current power supply, dimmable Casambi 220/240V-50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W /750 /800 /900 /1000 /1050mA - 38W



REQUIRED Power supply

Electrical

60.9222

Continuous current power supply of 12-20W, 110/240V - 50/60Hz with power current selected through adjustable 250mA - 12W / 350mA - 17W / 400mA - 19W / 450 / 500/ 550 / 600 / 700mA - 20W regulable Dali 1 & Dali 2



REQUIRED Power supply

60.9467

Continuous current power supply, Mains dimming (AC phase-cut dimming), leading & trailing edge 220/240V - 50/60Hz, 250mA - 12W / 300mA - 14W / 350mA - 17W / 400mA - 19W / 450 / 500 / 600 / 650 / 700 / 750 / 800 / 850 / 900mA - 20W



OPTIONAL Accessory

08.3309.14

Honeycomb



OPTIONAL Accessory

08.8627.68

Elliptical lens



OPTIONAL Accessory

08.3310.19

Flood lens

