

FLOS


03.3960.ANB Anodized Black

LED Squad 125 mm

Designed by FLOS Architectural



Direct/indirect lighting wall luminaire with LED. Remote transformer not included.
Dimmable.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Surface
Environment	Indoor dry location
LED type	Top LED
Lamp category	LED
Ilcos	No
Power (W)	3.2
Source flux (lm)	313
System flux (lm)	193

Physical

Colour	Anodized Black
Trim	No
Orientation	Fixed
Length (mm)	125
Net weight (kg)	0.045
IP internal	20
IP external	20

Download

[Mounting instructions](#) ZIP

Photometric Files

[LDT / IES](#) ZIP

Technical Drawings


[2D](#) ZIP

[3D](#) ZIP

[Bim](#) ZIP



Schematic light drawing



Beam Angle:	86°	
h(m)	E(lx)	D(m)
1	89	1.88
2	22	3.76
3	10	5.64
4	6	7.52
5	4	9.40

Photometric

Lighting type	Indirect, Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	86
Beam angle C90-270 (°)	99

Electrical

Insulation class	III
Main voltage (Vac)	24.00
Driver	Remote excluded
Dimmable	Yes
Dimming type	Dimmable
Emergency type	No

Notes

7 LEDs. Installation cables included: power cable 500 mm, connection cable 60 mm

Accessories & Power Supply



REQUIRED Accessory

60.8640

Dimmable 1-10V control unit with 1 channel for 24V LED modules. Max. 120W - 5A



REQUIRED Power supply

Electrical

60.9089

Electronic transformer with constant voltage (24V) for LED. 100/240V. 60W



REQUIRED Power supply

60.8703

Electronic transformer with constant voltage (24V) for LED. 100/240V. 25W



REQUIRED Accessory

Electrical

60.9766

Dimmable Dali 2 control unit for 12-48Vdc LED modules