

USO 100 50 Cove Lighting


LED - LED Module - 16 x 57.5W - 3000K - CRI> 90



Recessed soft ceiling luminaire. Direct lighting with LED lamps. See LED drivers.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications


Mounting	Ceiling recessed
Environment	Indoor dry location
LED type	LED Module
Lamp category	LED
Number of heads	16
Power (W)	57.5
Source flux (lm)	6000

Physical

Colour	Raw
Trim	No
Orientation	Fixed
Recessed depth (mm)	180
Length (mm)	1000
Net weight (kg)	25
IP internal	20



Schematic light drawing



Download

Mounting instructions [ZIP](#)

Photometric Files

LDT / IES [ZIP](#)

Technical Drawings

3D [ZIP](#)

Ecodesign and Energy Labelling



Replaceable (LED only)
light source by a
professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90

Electrical

Main voltage (Vac)	24
Driver	Remote excluded
Dimmable	No

Accessories & Power Supply



REQUIRED
Power supply
Electrical

60.8268
LED power supply source for remote installation in 24V/240W electric control panel. 100/240V



REQUIRED
Power supply
Electrical

60.9352
LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.



REQUIRED
Power supply
Electrical

60.9443
Power supply LED. 100W – 24V. 100-240V, 50-60Hz.




OPTIONAL
Accessory
Electrical

06.1016.00
Wiring 500mm for white module




OPTIONAL
Accessory
Electrical

08.8297.00
2 Meters Prolongation Cable for white modules



OPTIONAL
Power supply
Electrical

06.1019.00E
White DALI Master Interface Dimmable




OPTIONAL
Power supply
Electrical

06.1020.00E
White DALI, DMX & RF Slave Interface Dimmable



OPTIONAL
Power supply
Electrical

60.9658
White&RGB Casambi Wireless Dimmable Interface



OPTIONAL

Electrical

06.1022.00E

Dimmable Interface. 1-10V

interface with two 500mm feed
cable for white LED modules with
fast connection