

USO 2500 Cove Lighting



Recessed soft ceiling luminaire. Direct lighting with LED lamps. See LED drivers.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling recessed
Environment	Indoor dry location
LED type	LED Module
Lamp category	LED
Number of heads	54
Power (W)	194
Source flux (lm)	20250

Physical

Colour	Raw
Trim	No
Orientation	Fixed
Recessed depth (mm)	210
Length (mm)	3000
Net weight (kg)	185
IP internal	20



Download

Mounting instructions [ZIP](#)

Photometric Files


LDT / IES [ZIP](#)

Technical Drawings

3D [ZIP](#)



Schematic light drawing



Ecodesign and Energy Labelling



Replaceable (LED only)
light source by a
professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90

Electrical

Main voltage (Vac)	24
Driver	Remote excluded
Dimmable	No

Notes

Delivered in two pieces.

Accessories & Power Supply



REQUIRED
Power supply
Electrical

60.8268
LED power supply source for remote installation in 24V/240W electric control panel. 100/240V



REQUIRED
Power supply
Electrical

60.9352
LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.




OPTIONAL
Accessory
Electrical

06.1016.00
Wiring 500mm for white module




OPTIONAL
Accessory
Electrical

08.8297.00
2 Meters Prolongation Cable for white modules



OPTIONAL
Power supply
Electrical

06.1019.00E
White DALI Master Interface Dimmable




OPTIONAL
Power supply
Electrical

06.1020.00E
White DALI, DMX & RF Slave Interface Dimmable



OPTIONAL
Power supply
Electrical

60.9658
White&RGB Casambi Wireless Dimmable Interface



OPTIONAL
Electrical

06.1022.00E
Dimmable Interface. 1-10V interface with two 500mm feed cable for white LED modules with fast connection