

Solid Pure Ceiling/Wall No Dimmable

Designed by Knud Holscher, 2014




LED - LED array - 35W - 2783lm - 3000K - CRI> 90 - Beam° 45

Spotlight to be installed on ceiling/wall with LED light source. 220-240V, 50-60Hz power supply included.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Surface
Enviroment	Indoor dry location
LED type	LED array
Lamp category	LED
Ilcos	No
Number of heads	1
Power (W)	35
Source flux (lm)	3435
System flux (lm)	2783

Physical

Colour	White
Trim	No
Orientation	Adjustable
Rotation (°)	360
Net weight (kg)	1.90
IP internal	20
IP external	20

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)


Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	45
Beam angle C90-270 (°)	45

Electrical

Insulation class	I
Frequency (Hz)	50/60
Driver	Integrated
Dimmable	No
Dimming type	Non Dimmable
Emergency type	No


Accessories & Power Supply



OPTIONAL
Accessory

08.8763.14


Honeycomb anti-glare screen



OPTIONAL
Accessory

08.8766.64.OD


Blue filter



OPTIONAL
Accessory

08.8766.65.OD


Sky blue filter



OPTIONAL
Accessory

08.8766.66.OD

Amber filter



OPTIONAL
Accessory

08.8766.67.OD

Red filter



OPTIONAL
Accessory

08.8768.14

Holding ring