

Suspension Cone Ø 400 NEW

Designed by Vincent Van Duysen, 2020



LED - Top LED - 41W - 2270lm - 2700K - CRI> 90 - Beam° 63

Suspended luminaire with locking system integrated, to be installed in the Infra-Structure Episode 2 system. Each lighting element is completed by a long 4m electrical cable equipped with an output microconnector.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling surface
Enviroment	Indoor dry location
Light source type	LED
LED type	Top LED
Lamp category	LED
Iicos	No
Bulb finish	Opal
Number of heads	1
Power (W)	41
System power (W)	41
Source flux (lm)	0
System flux (lm)	2270
Efficacy (lm/W)	55.37

Physical

Colour	White
Orientation	Fixed
Spot diameter (mm)	400
Net weight (kg)	2.85
IP internal	20
IP external	20



Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)

[Bim](#) [↓ ZIP](#)


Ecodesign and Energy Labelling



Replaceable (LED only)
light source by a
professional



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B50
Beam angle C0-180 (°)	63
Beam angle C90-270 (°)	63
UGR _L	17

Electrical

Insulation class	III
Forward voltage (V)	48
Driver	Remote excluded
Dimmable	Yes
Emergency type	No

Accessories & Power Supply



REQUIRED
Power supply
Electrical

60.9170
LED power supply source for remote installation, 48V/120W. 220/240 Vac



REQUIRED
Power supply
Electrical

60.8919
LED Power Supply Source for remote installation. 48V/320W. 100/240 Vac



REQUIRED
Power supply
Electrical

60.9607
LED Power Supply Source for remote installation. 48V. 100Vac (150W)-240Vac (200W)



OPTIONAL
Control interface
Electrical

60.9392
Casambi controller. Use only with 60.9361. Requires 1-10V or Dali driver. It must be ordered separately



OPTIONAL
Control interface
Electrical

60.9395
LED module 1/10V dimmable control unit for 12 to 48V equipment.



OPTIONAL
Control interface
Electrical

60.9678
Dimmable Dali control unit for 12-48Vdc LED modules