


The Tracking Magnet Surface/Suspension Profile Casambi / On Board Dimmer compatible

Designed by FLOS Architectural, 2018



Electromechanical profile for surface-mounting, available in lengths from 1m to 3m.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Surface and suspension
Environment	Indoor dry location
Ilcos	No

Physical

Colour	White
Trim	No
Field cuttable	Yes
Length (mm)	1000
Net weight (kg)	1.22
IP internal	20
IP external	20



Download

Mounting instructions

[ZIP](#)



Electrical

Main voltage (Vac)	48
Forward voltage (V)	48
Driver	Remote
Dimmable	Yes
Dimming type	Dimmer on board, Dimmable Casambi
Emergency type	No

Notes

Version compatible with "On board dimmer" luminaries and version compatible with system controlled luminaries (DALI, 1-10V, FLOS SMART CONTROL) available. Corners, connectors and accessories common for the two profile versions. Feed connector, intermediated connector, end-caps and attachment accessories to be ordered separately. Mechanical 90° corners available in the same plane (symmetrical element for left and right corner) and 90° symmetrical internal corners in a different plane. Intermediate connectors to be ordered separately if electrical continuity on corners is required. Corners do not admit installation of spots.

Accessories & Power Supply



OPTIONAL
Accessory

Electrical

06.0157.00
4-pole, 0.75 mm² section, 4-meter long, transparent power cable




OPTIONAL
Accessory

06.5017.40
The Tracking Magnet Surface/Suspension Profile End Caps




OPTIONAL
Electrical

06.1988.40
Multifunction Smart Device for Tracking Magnet & Infra-Structure



OPTIONAL
Power supply

Electrical
08.0600.14
Surface power supply with 320W / 48Vdc driver included



OPTIONAL
Power supply

Electrical

08.0600.40
Surface power supply with 320W / 48Vdc driver included



OPTIONAL
Accessory

Electrical


08.0611.14
The Tracking Magnet Profile Feed Connector



OPTIONAL
Accessory

Electrical

08.0612.14
The Tracking Magnet Profile Intermediate Connector Straight



OPTIONAL
Accessory

Mounting

08.0615.00
Ceiling fixing kit



OPTIONAL
Accessory
Mounting

08.0616.00
Ceiling fixing kit



OPTIONAL
Accessory
Mounting

08.8634.00
4m suspension steel cable



OPTIONAL
Mounting

08.8883.14A
Surface rose



OPTIONAL
Mounting

08.8883.40A
Surface rose



OPTIONAL
Electrical

08.8889.14
Recessed power supply rose



OPTIONAL
Electrical

08.8889.40
Recessed power supply rose



OPTIONAL
Accessory
Mounting

60.3014.11
Suspension rod with 1m rose.
M6 thread



OPTIONAL
Accessory
Mounting

60.3014.14
Suspension rod with 1m rose.
M6 thread



OPTIONAL
Mounting

60.3097.11

1 m suspension rod with ceiling
rose with m6 thread



OPTIONAL
Mounting

60.3097.14

1 m suspension rod with ceiling
rose with m6 thread



OPTIONAL
Power supply
Electrical

60.8919

LED Power Supply Source for
remote installation. 48V/320W.
100/240 Vac



OPTIONAL
Power supply
Electrical

60.9170

LED power supply source for
remote installation, 48V/120W.
220/240 Vac



OPTIONAL
Power supply
Electrical

60.9607

LED Power Supply Source for
remote installation. 48V. 100Vac
(150W)-240Vac (200W)