




N10U303G30B White

## In-Finity 100 Suspension Up & Down 3000K General Lighting

Designed by FLOS Architectural, 2015



LED modular system for suspended installation, including LED luminaires, aluminum installation profile, and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules. Suspension kit included.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

|                 |                     |
|-----------------|---------------------|
| Mounting        | Suspension          |
| Enviroment      | Indoor dry location |
| LED type        | Top LED             |
| Lamp category   | LED                 |
| Ilcos           | No                  |
| Number of heads | 1                   |
| Power (W)       | 119                 |

### Physical

|                 |       |
|-----------------|-------|
| Colour          | White |
| Trim            | No    |
| Orientation     | Fixed |
| Length (mm)     | 3095  |
| Net weight (kg) | 21.4  |
| IP internal     | 20    |
| IP external     | 20    |

### Download

[Mounting instructions](#)  PDF

### Photometric Files

[LDT / IES](#)  ZIP


### Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP



Schematic light drawing



Photometric

|                    |                  |
|--------------------|------------------|
| Lighting type      | Indirect, Direct |
| Light distribution | Symmetric        |
| CCT (K)            | 3000             |
| CRI>               | 80               |

Electrical

|                  |              |
|------------------|--------------|
| Insulation class | I            |
| Frequency (Hz)   | 50/60        |
| Driver           | Integrated   |
| Dimmable         | No           |
| Dimming type     | Non Dimmable |
| Emergency type   | No           |

Notes

Opal Diffuser: Diffuse, glare free and uniform lighting throughout the room. /  
Emergency: Emergency Module available in all versions, length 1405 mm. In normal use, it uses the same power consumption as the standard In-Finity. In emergency use, it emits 10% of normal use during 3 hours. Endcaps: must be ordered separately. Consult Flos Architectural team for a configuration without end caps.

Accessories & Power Supply



OPTIONAL  
Accessory

08.0030

Suspension kit



OPTIONAL  
Accessory

08.0031.00

Power supply rose



OPTIONAL  
Accessory

08.9058.02

Metal cover. Suspension Up &  
Down. 100 mm (Colour Anodized  
Grey)



OPTIONAL  
Accessory

08.9058.40

Metal cover. Suspension Up &  
Down. 100 mm (Colour White)



OPTIONAL  
Accessory

08.9058.NS

Metal cover. Suspension Up &  
Down. 100 mm (Colour Black)



OPTIONAL  
Accessory

08.0111.00

500 mm opal diffuser. Diffuse,  
glare free and uniform lighting  
throughout the room