

FLOS

03.3902.30E White

LED Curtain 600 mm UPGRADE

Designed by FLOS Architectural, 2016



Recessed luminaire for direct lighting with LED. Elliptical lens 12°x52° incorporated.
Remote transformer not included

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Recessed
Enviroment	Indoor dry location
LED type	Power LED
Lamp category	LED
Lamp holder	LED Module
Power (W)	17.3
Source flux (lm)	1906
System flux (lm)	931

Physical

Colour	White
Trim	Yes
Orientation	Fixed
Recessed depth (mm)	42
Length (mm)	600
Net weight (kg)	0.6
Package volume (m3)	0.01
IP internal	20



Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)


[Bim](#) [↓ ZIP](#)



Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class **G**

Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
Beam angle C0-180 (°)	12
Beam angle C90-270 (°)	52

Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	24
Driver	Remote excluded
Dimmable	Yes
Dimming type	Non Dimmable, Dimmable 1-10V, Dimmable DALI 1

Notes

12 LEDs.

Accessories & Power Supply



REQUIRED
Accessory

06.1034.00

Power cable L: 500 mm



REQUIRED
Power supply

60.8515

Electronic transformer with constant voltage (24V) for LED. 60W. 100/240V. For independent use



REQUIRED
Accessory

60.8640

Dimmable 1-10V control unit with 1 channel for 24V LED modules. Max. 120W - 5A



REQUIRED
Power supply

Electrical

60.9089

Electronic transformer with constant voltage (24V) for LED. 100/240V. 60W



REQUIRED
Power supply

Electrical

60.9407

Electronic transformer with constant voltage (24V) for LED. 100/240V. 120W



REQUIRED
Power supply

60.8703

Electronic transformer with constant voltage (24V) for LED. 100/240V. 25W



REQUIRED
Power supply

60.8407

Dimmable DALI control unit with 3 channel for 24V LED modules. Power supply not included. Max. 120W - 5A.



OPTIONAL
Accessory

06.1032.00

Connection cable L: 100 mm



OPTIONAL
Accessory

06.1033.00

Connection cable L: 500 mm