

FLOS

SA.5069.3.0V3 Violet

APPS Info

Designed by Jorge Herrera, 2013



LED - LED array - 4W - CRI> 80

Recessed sign luminaire for indoor application. Power supply source not included: continuous current power supply of 350mA. 220/240V, 50/60Hz.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Wall recessed
Enviroment	Indoor dry location
LED type	LED array
Lamp category	LED
Ilcos	No
Power (W)	4
Source flux (lm)	350

Physical

Colour	Violet
Trim	No
Orientation	Fixed
Net weight (kg)	0.9
IP internal	20
IP external	20



Download

Mounting instructions

PDF

UK CA	IP 20	IP 20
----------	----------	----------

Photometric

Lighting type	Indirect
Light distribution	Symmetric
CRI>	80

Electrical

Driver	Remote excluded
Dimmable	No
Dimming type	Non Dimmable
Emergency type	No

<https://professional.flos.com/en/global/product/apps-info-sa.5069.3.0v3/>

SA.5069.3.0V3

©2022 Flos - P.IVA 00290820174 - 3/12/2023

professional.flos.com | info@flos.com 1/3

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order to improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

Accessories & Power Supply



OPTIONAL
Accessory

60.8402

Electrical