

FLOS

SA.5102.1A Lighting blue

G-O IN

Designed by Jorge Herrera, 2017




LED - Top LED - 1.2W

Recessed sign luminaire for indoor application. Power supply source not included: electronic transformer with constant voltage (24V) for LED. 220/240V, 50/60Hz. It includes 1000mm power supply cable.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Wall recessed
Enviroment	Indoor dry location
LED type	Top LED
Lamp category	LED
Ilcos	No
Power (W)	1.2
Source flux (lm)	105

Physical

Colour	Lighting blue
Trim	No
Orientation	Fixed
Net weight (kg)	0.7
IP internal	20
IP external	20

Download

Mounting instructions

↓ PDF

UK	IP	IP
CA	20	20

Photometric

Lighting type	Indirect, Direct
Light distribution	Symmetric

Electrical

Main voltage (Vac)	24.00
Driver	Remote excluded
Dimmable	No
Dimming type	Non Dimmable
Emergency type	No

Accessories & Power Supply



REQUIRED
Accessory

60.8640

Dimmable 1-10V control unit with 1 channel for 24V LED modules. Max. 120W - 5A



REQUIRED
Power supply

60.9157

Electronic transformer with constant voltage (24V) for LED. 8W, 110/240V, 50/60H



REQUIRED
Power supply

60.8703

Electronic transformer with constant voltage (24V) for LED. 100/240V. 25W



REQUIRED
Accessory

Electrical

60.9766

Dimmable Dali 2 control unit for 12-48Vdc LED modules



OPTIONAL
Power supply

60.8079

Electronic transformer with constant voltage (24V) for LED. 8W, 220/240V, 50/60H